

IRC 12.45 m Racer Cruiser

Specification 01-2023

Туре

12.45 m production dual purpose yacht aimed at providing competitive IRC performance and comfortable accommodation.

Desian

Mills Yacht Design, Mark Mills www.mills-design.com

Design Category

CE category A 10

Dimensions

Dimensions	
Hull length	12.45 m
LWL	10.66 m
Beam max	3.75 m
Draft	2.65/2.55 m
Displacement	6.780/6.940 kg
Ballast	3.220/3.380 kg
I	16.97 m
J	4.82 m
Р	16.58 m
E	5.90 m
ISP	18.40 m
STL	5.50 m

Construction

E-glass, PVC core, epoxy vinylester resin Vacuum assisted resin infusion Gelcoat finish on hull, deck and internal structure Composite structural IGU for interior arrangement

Keel

580 kg SG iron fin with 2640/2800 kg lead/antimony bulb, total 3240/3380 kg (approximate), adjustable draft and bulb weight.

Rudder and Steering

Carbon fiber rudder stock Jefa self-aligning rudder bearings Carbonautica 1000 mm composite twin wheels

Deck

Harken winches: 2 x primary winches 50.2 STP 2 x main sheet winches 50.2 STP 2 x halyard winches 46.2 STP Harken deck gear package: 2:1 mainsheet to winch Mainsheet traveller and track, blocks for 6:1 windward sheeting traveler purchase system Longitudinal jib tracks, ball bearing cars and blocks for 12:1 purchase system Spinnaker sheet and deflector blocks Halyard lead blocks 7 Spinlock clutches Custom alloy fairleads 4 opening portlights 3 opening hatches 1 opening round foredeck hatch Custom tempered laminated cabin windows SS stanchions, pulpits and pushpits 5 mm 1x19 SS lifelines Custom stainless steel chainplates recessed in hull Anchor locker with drain, provision for mounting the windlass in the locker 40 mm molded toe rail to mast Composite mast collar Recessed companionway sliding hatch Locker for gas bottle

Plastimo 135 mm compass

Mast and Rig

Axxon Composites carbon fiber mast Alloy spreaders Rod rigging Integral hydraulic mast jack Carbon fiber boom Carbon fiber spinnaker pole Hydraulic integral backstay adjuster Racing head stay foil twin groove Harken Carbo black Provision for: 1 main halyard 2:1 2 masthead spinnaker halyard 1 wing spinnaker/jib halyard to spectacle at I height 1 CI I height jib halyard 1 pole lift 1 m below I

Engine

Yanmar 30 Hp diesel engine with SD25 sail drive Vetus 110 I diesel tank, level indicator, fuel filter, water separator Diesel fill on deck Radice 2 bladed folding propellers Single lever engine control

Flectrical 12 volt DC

Victron Energy 2x110 Ah AGM house batteries Victron Energy 1x100 Ah AGM starter battery LED interior lights LED navigation lights

Plumbing

200 I flexible fresh water tank Pressurized water system Hand basin in head Galley sink, mixer tap Jabsco manual bilge pump 3000 l/h Rule electric bilge pump 7570 l/h Jabsco marine toilet Fresh water fill on deck

Interior

All bulkheads and other interior components in PVC foam cored composite White colored gelcoat surfaces for ease of maintenance, lightweight and modern appearance Honeycomb cored satin varnished natural oak cabin doors and cabinet doors Custom lightweight alloy cabinets to match alloy door frames, alloy portlights trims Custom alloy handrails Southco satin polished door handles High density foam cushions, Sunbrella upholstery Central salon area with settees port & starboard, large wet locker starboard, cabinets with doors on P&S Enclosed head to port forward of mast, s/s hand basin, shower, china bowl, cabinet Forward cabin with double berth, wardrobe, large space under the bed, naturel light from foredeck hatch Large double berth cabin port & starboard aft, hanging lockers, double portlights . Galley to port by companionway, s/s sink, gimballing cooker, refrigerator compartment Navigation station to starboard of companionway Lightweight composite companionway ladder for easy access to engine